

aprilia®

RS4 125 RS4 50



125/50







START IN POLE POSITION

DIRECTLY FROM THE ON-TRACK EXPERIENCE AND TECHNOLOGICAL RESEARCH OF WORLD CHAMPIONS, TWO MOTORBIKES DEDICATED TO YOUNGSTERS THAT WANT TO EXPERIENCE THE MOST EXTRAORDINARY SPORTING THRILLS. DESIGN AND COLOURS THAT ECHO THOSE OF THE RSV4, THE NO.1 MOTORBIKE IN THE SUPERBIKE WORLD CHAMPIONSHIP. CUTTING EDGE TECHNOLOGY, TOP-LEVEL EQUIPMENT, RACING SOLUTIONS FOR AN EXCITING RIDING EXPERIENCE: APRILIA SETS A NEW STANDARD AND WINS IN EVERY COMPARISON.

RACING SOLUTIONS

For the best weight distribution, the RS4 125 exhaust is fully integrated into the bottom of the fairing, allowing for an even more effective ride. Not only that, the licence plate and turn signals are designed to be easily removed, the best configuration for use on the track.





RS REVOLUTION

RS4 125, FOR THE FIRST TIME WITH A FOUR STROKE 125CC ENGINE WITH ELECTRONIC INJECTION, 4 VALVES AND DOUBLE OVERHEAD CAMSHAFFOR EVEN MORE TECHNOLOGICALLY ADVANCED, ECOLOGICAL AND CLEAN CONSUMPTION. RS4 50 WITH A LATEST GENERATION TWO-STROKE ENGINE THAT PERFORMS AT THE TOP OF THE CLASS. CHOOSE YOUR OWN CUSTOM MOTORBIKE AND SET OUT ON YOUR ROUTE TO GREATNESS.

WINNING TECHNOLOG

Upside Down 41mm fork, front brake with 4 piston radial pin, Grand Prix rim wheels: with RS4 125 and RS4 50 you get the maximum, in every detail.



UNMISTAKABLE LOOK

Tested in the wind tunnel, the perfectly aerodynamic fairing, top fairing and tail fairing ensure maximum protection and minimum air resistance, giving the motorbike an unbeatable, real racing look.

SHARP LOOK

The aggressive front headlight assembly faithfully reproduces the triple headlamp of the Aprilia supersport large engine capacity motorbikes. RS4 125 RS4 50 are also unmistakable in the rear area, thanks to the innovative LED tail light.





TRACK CHASSIS

Made of aluminium, the frame of the two motorbikes is derived from the successful experience of Aprilia in the Moto GP championship races, combining high rigidity with a surprising lightness.

WINNING ACCESSORIES

Make your RS4 even more unique and exciting, by choosing from a range of accessories made specifically for you, to experience on the circuit or on the road all the thrills of the Superbike Championship. Discover all the original Aprilia accessories at: www.aprilia.com

OUTSTANDING INSTRUMENT PANEL

The Analogue Digital instrument panel with comprehensive and highly readable information, comes directly from its elder sibling RSV4, the entire Aprilia experience in the

INTELLIGENT DETAILS

With the hook and release system, it takes just a moment to replace the seat for the passenger with the











RS4 50



Colour schemes available on the RS4 125 and RS4 50

RS4	S F	25

	110+ 125		1104 30
Engine type	Four stroke liquid cooled single-cylinder with electronic injection and 4 valves. Euro 3.	Engine type	Single-cylinder, 2 stroke, liquid cooling. Euro 2
Bore and stroke	Double overhead camshaft - DOHC	Engine capacity	39.86 x 40 mm
Engine capacity	58 X 47 mm	Timing system	49.9 cc
Timing system	124.8 cc	Compression ratio	11.5 :1
Compression ratio	12.5 ± 0.5:1	ECU	Dell'Orto PHVA – 17.5
ECU	Magneti Marelli MIU G3 32 MM diam.	Ignition	Electronic C.D.I.
Ignition	Electronic with CDI capacity discharge	Starter	Electric
Starter	Electric	Alternator	12V – 6Ah
Alternator	13V - 235W	Transmission	6 speed automatic mixer:
Lubrication	Wet crankcase		1st 11/34, 2nd 15/30, 3rd 18/27, 4th 20/24, 5th 22/23, 6th 23/22
Transmission	6 speed:	Primary drive	Gears: 21/78
	1 st 11/33, 2 nd 15/30, 3 rd 18/27, 4 th 20/24, ^{5th} 25/27, 6 th 23/22	Final drive	Chain: 11/53
Primary drive	Gears: 69/29	Clutch	Multiplate wet clutch
Final drive	Chain: 60/13	Frame	Twin spar aluminium frame
Clutch	Multiple discs, in oil bath	Front suspension	41 mm diameter Upside Down fork, wheel travel 110 mm
Frame	Aluminium perimeter frame	Rear suspension	Asymmetric swingarm with monoshock, wheel travel 130 mm
Front suspension	41 mm diameter Upside Down fork, wheel travel 110 mm	Brakes	Front: 300 mm diameter stainless steel disc with radial 4 piston calliper
Rear suspension	Asymmetric swingarm with monoshock, wheel travel 130 mm		Rear: 218 mm diameter stainless steel disc and calliper with single 30 mm diameter piston
	Front: 300 mm diameter stainless steel disc with radial 4 piston calliper.	Wheel rims	in light alloy with 6 split spokes, with sealing profile for tubeless tyres;
	Rear: 218 mm diameter stainless steel disc and calliper with single 30 mm diameter piston		front: 2.75 x 17"; rear: 3.50 x 17"
Wheel rims	in light alloy with 6 split spokes, with sealing profile for tubeless tyres;	Tyres	Front: 110/80 - 17", rear: 130/70 - 17"
	front: 2.75 x 17"; rear: 3.50 x 17"	Dimensions	Max length 1953 mm, Max Width 740 mm,
Tyres	Front: 110/80 - 17", rear: 130/70 - 17"		Saddle Height 820 mm, Max height at top fairing 1,138 mm,
Dimensions	Length max 1953 mm, Width max 740 mm, saddle Height 820 mm,		Wheelbase 1,350 mm
	Max height at top fairing 1,138 mm, Wheelbase 1,350 mm	Fuel tank capacity	14.5 litres (including 3.5 litre reserve)
Fuel tank capacity	14.5 litres (including 3.5 litre reserve)		



RS4 125 is an environmentally friendly vehicle compliant with Euro 3 regulations for exhaust and noise emissions.



RS4 50 is an environmentally friendly vehicle compliant with Euro 2 current regulations.

Dealer

