





hold two helmets, one flip up, or a laptop bag.



## SRMAX 300/125







## SR MAX 300 i.e.

Engine	QUASAR 4-stroke single cylinder	Engine
Engine capacity	278 cc	Engine capacity
Bore / Stroke	75 mm / 63 mm	Bore / Stroke
Power	22.4 hp at 7,250 rpm	Power
Torque	23 Nm at 6,000 rpm	Torque
Valve timing system	Single overhead camshaft (SOHC) - 4 valves	Valve timing system
Fuel system	Electronic injection	Fuel system
Cooling	Liquid	Cooling
Lubrication	Wet sump	Lubrication
Starter	Electric	Starter
Transmission	CVT with torque server	Transmission
Clutch	Automatic, centrifugal dry clutch	Clutch
Frame	Double cradle in high strength tubular steel	Frame
Front suspension	35 mm hydraulic telescopic fork	Front suspension
Rear suspension	Double shock absorber with three-position spring preload adjustment	Rear suspension
Front brake	260 mm Ø disc	Front brake
Rear brake	240 mm Ø disc	Rear brake
Front wheel rim	Aluminium alloy 15" x 3.00	Front wheel rim
Rear wheel rim	Aluminium alloy 14" x 3.50	Rear wheel rim
Front tyre	Tubeless 120/70-15"	Front tyre
Rear tyre	Tubeless 140/60-14"	Rear tyre
Length / Width	2,110 mm / 780 mm	Length / Width
Wheelbase / Saddle height	1,515 mm / 815 mm	Wheelbase / Saddle height
Fuel tank capacity	15 litres (including 2.8 litre reserve)	Fuel tank capacity
Emissions compliance	Euro 3	Emissions compliance

## SR MAX 125 i.e.

Engine	4-stroke single cylinder	
Engine capacity	124cc	
Bore / Stroke	57 mm / 48.6 mm	
Power	15 hp at 9,250 rpm	
Torque	12 Nm at 8,000 rpm	
Valve timing system	Single overhead camshaft (SOHC) - 4 valves	
Fuel system	Electronic injection	
Cooling	Liquid	
Lubrication	Wet sump	
Starter	Electric	
Transmission	CVT with torque server	
Clutch	Automatic, centrifugal dry clutch	
Frame	Double cradle in high strength tubular steel	
Front suspension	35 mm hydraulic telescopic fork	
Rear suspension	Double shock absorber with three-position spring preload adjustment	
Front brake	260 mm Ø disc	
Rear brake	240 mm Ø disc	
Front wheel rim	Aluminium alloy 15" x 3.00	
Rear wheel rim	Aluminium alloy 14" x 3.50	
Front tyre	Tubeless 120/70-15"	
Rear tyre	Tubeless 140/60-14"	
Length / Width	2,110 mm / 780 mm	
Wheelbase / Saddle height	1,515 mm / 815 mm	
Fuel tank capacity	15 litres (including 2.8 litre reserve)	
Emissions compliance	Euro 3	



SR MAX is an environmentally friendly vehicle compliant with Euro 3 regulations for exhaust and noise emissions.

Drive safely always wearing a helmet and protective clothing. Observe the laws of the road and respect the environment. Carefully read the owners' handbook. Photographs, technical data, specifications and colours shown in this brochure refer to the Italian market version and may be subject to change without prior notice. Ask your official Aprilia dealers for full details. In order to maintain your machine in a safe and efficient manner, always demand official Aprilia Spare Parts, which are guaranteed by Aprilia Quality Service in respect of current legislation. E & O E. Aprilia offers Aprilia Road Assistance, a call centre available 24 hours a day for information and road rescue. E. & O.E. Aprilia reserves the right to change colour/ specification without prior notice.







The



trademark is the property of Piaggio & C. S.p.A.